OUTPOST LED I OUTDOOR WALL MOUNT

SM866401 | SM866403 | SM866405

- Aluminum Construction
- Available in Incandescent or LED
- Available in Brushed Aluminum or Black
- Gasketed glass lens for direct water contact applications












PRODUCT DESCRIPTION

Classic cylinder up and down lights provide directional light without glare. Available in 3 sizes with both incandescent and LED versions. Available in Architectural Bronze, Aluminum, or Black.



EXT.

LAMPING MEASUREMENTS

OKLINLIAIS	LAMII III O				
		LUMENS			
DIMENSION	BULB TYPE	RATED	DEL	DIMMABLE	INPUT
5"W x 7.25"H x 6.25"Ext.XX	1 LED x 8W AC Integrated E26	360	240	NO	120V
5"W x 15"H x 6.25"Ext.	2 LED x 16W AC Integrated E26	260	200	NO	120V
5"W x 22"H x 6.25"Ext.	2 LED x 16W AC Integrated E26	210	150	NO	120V
	DIMENSION 5"W x 7.25"H x 6.25"Ext.XX 5"W x 15"H x 6.25"Ext.	DIMENSION BULB TYPE 5"W x 7.25"H x 6.25"Ext.XX 1 LED x 8W AC Integrated E26 5"W x 15"H x 6.25"Ext. 2 LED x 16W AC Integrated E26	DIMENSION BULB TYPE RATED 5"W x 7.25"H x 6.25"Ext.XX 1 LED x 8W AC Integrated E26 360 5"W x 15"H x 6.25"Ext. 2 LED x 16W AC Integrated E26 260	DIMENSION BULB TYPE RATED DEL 5"W x 7.25"H x 6.25"Ext.XX 1 LED x 8W AC Integrated E26 360 240 5"W x 15"H x 6.25"Ext. 2 LED x 16W AC Integrated E26 260 200	DIMENSION BULB TYPE RATED DEL DIMMABLE 5"W x 7.25"H x 6.25"Ext.XX 1 LED x 8W AC Integrated E26 360 240 NO 5"W x 15"H x 6.25"Ext. 2 LED x 16W AC Integrated E26 260 200 NO

FINISHES OPTION

Black Bronze Brushed Aluminum

MATERIAL

Aluminum

RATINGS *Dark Sky Optional **cETLus** Wet Location







ADDITIONAL

INSTALL UP/DOWN: UP OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consulta qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments