COUNTERMAX MX-L-120-LO | UNDERCABINET SM869901 / SM869902 / SM869903 / SM869904

- 40,000 rated life hours
- Linkable end-to-end or with MX Interlink5
- Value pricing
- Frosted Lens
- CRI 80+
- Suitable for Dry location
- FTL CFTL




Job Name:

Quantity:

PRODUCT DESCRIPTION

The MX-L120-LO is our economy LED Under counter. It features an extruded aluminum body with anodized finishes and a frosted acrylic lens. Its easy mount end caps makes for easy and quick installation without the use of clips. Can be direct wired with the use of direct wire box or plugged directly into outlet.



MEASUREMENTS

MILASUN	HANGING WEIGHT		
MODEL			
SM869901	10"L x 2"W x 1"H	0.26 lb	
SM869902	21"L x 2"W x 1"H	0.40 lb	
SM869903	30"L x 2"W x 1"H	0.62 lb	
SM869904	40"L x 2"W x 1"H	0.77 lb	

LAMPING

COLOR									
	MODEL	BULB TYPE	TEMP.	LUMENS	CRI	INPUT	DIMMABLE		
	SM869901	(1) 6W PCB LED (Integrated)	3000K	390	+08	120V	No		
	SM869902	(1) 10W PCB LED (Integrated)	3000K	650	+08	120V	No		
	SM869903	(1) 12W PCB LED (Integrated)	3000K	780	+08	120V	No		
	SM869904	(1) 14W PCB LED (Integrated)	3000K	910	+08	120V	No		

ACCESSORIES



SM869958 BK, **WT**MXInterLink5 Direct Wire Box
6.5"L x 2.75"W x 1"H



SM563255 Plastic Wire Clips (Package of 10) 1"L x 0.5"W x 0.25"H



MXInterLink4 Connector Cord 9" **SM869951** BK, **WT** 18" **SM869952** BK, **WT** 24" **SM869953** BK, **WT**



SM869954 BK, WT MXInterLink5 Connector Cord 72"

• Includes on/off switch

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

White (WT)

Job Type:

Comments:

Anodized Bronze (BRZ)

MATERIAL:

Aluminum + Acrylic

AVAILABLE SIZE:

10" | 21" | 30" | 40"

INCLUDES

• Two captured mounting screws

RATINGS:

ETL cETL DRY Location



5

ADDITIONAL:

RATED LIFE: 40,000 Hours

OPERATING TEMP: -20° C (-4°), 40°C (104°F)

PHOTOMETRIC: Report Found Online

